according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU

Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

date of compilation: 2015-09-24 article number: 7115 Version: 1.0 en

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier 1.1

Identification of the substance **Toluene**

Article number 7115

Registration number (REACH) 01-2119471310-51-xxxx

Index No 601-021-00-3 EC number 203-625-9 CAS number 108-88-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: laboratory chemical

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone: +49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data : Department Health, Safety and Environment

sheet

e-mail (competent person) : sicherheit@carlroth.de

1.4 **Emergency telephone number**

> Emergency information service Poison Centre Munich: +49/(0)89 19240

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification according to Regulation (EC) No 1272/2008 (CLP)

Classification acc. to GHS

Section	Hazard class	Hazard class and cat- egory	Hazard state- ment
2.6	flammable liquids	(Flam. Liq. 2)	H225
3.2	skin corrosion/irritation	(Skin Irrit. 2)	H315
3.7	reproductive toxicity	(Repr. 2)	H361d
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	(STOT SE 3)	H336
3.9	specific target organ toxicity - repeated exposure	(STOT RE 2)	H373
3.10	aspiration hazard	(Asp. Tox. 1)	H304

United Kingdom (en) Page 1 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

Remarks

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Narcotic effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

Pictograms







Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure (if

inhaled).

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves/eye protection.

Precautionary statements - response

P302+P352 IF ON SKIN: Wash with plenty of soap and water. P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

For professional users only

Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)







H304 May be fatal if swallowed and enters airways. H361d Suspected of damaging the unborn child.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

United Kingdom (en) Page 2 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Toluene

Index No 601-021-00-3

Registration number (REACH) 01-2119471310-51-xxxx

EC number 203-625-9
CAS number 108-88-3
Molecular formula C7H8

Molar mass 92,14 ^g/_{mol}

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

After eye contact: Conjunctival redness of the eyes, Causes slight to moderate irritation, Following skin contact: Has degreasing effect on the skin, Irritant effects,

After ingestion: Vomiting, Aspiration hazard,

Following inhalation: Cough, Headaches and dizziness may occur, Deficits in perception and coordination, reaction time, or sleepiness, Poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness

United Kingdom (en) Page 3 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

4.3 Indication of any immediate medical attention and special treatment needed

To supervise the blood circulation. Subsequent observance for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings water spray, foam, dry extinguishing powder, carbon dioxide (CO2)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. Solvent vapours are heavier than air and may spread along floors. Vapours can form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

Special protective equipment for firefighters

Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles. Self-contained breathing apparatus (SCBA). Self-contained breathing apparatus (EN 133).

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Avoid contact with skin, eyes and clothes. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it. Explosive properties.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

United Kingdom (en) Page 4 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

SECTION 7: Handling and storage

Precautions for safe handling

Provision of sufficient ventilation.

• Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Nota- tion	Identifier	TWA [mg/m³]	STEL [mg/m³]	Source
EU	toluene	108-88-3		IOELV	192	384	2006/15/EC
UK	toluene	108-88-3		WEL	191	384	EH40/2005

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period unless otherwise specified TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

United Kingdom (en) Page 5 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

Relevant DNELs/DMELs/PNECs and other threshold levels

human health values

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	384 mg/m³	human, inhalatory	worker (industry)	acute - local effects
DNEL	384 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	192 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
DNEL	384 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
DNEL	192 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects

environmental values

Endpoint	Threshold level	Environmental compartment	Exposure time
PNEC	0,68 mg/l	freshwater	short-term (single instance)
PNEC	0,68 mg/l	marine water	short-term (single instance)
PNEC	13,61 mg/l	sewage treatment plant (STP)	short-term (single instance)
PNEC	16,39 mg/kg	freshwater sediment	short-term (single instance)
PNEC	16,39 mg/kg	marine sediment	short-term (single instance)
PNEC	2,89 mg/kg	soil	short-term (single instance)
PNEC	0,68 mg/l	water	continuous

8.2 Exposure controls

Individual protection measures (personal protective equipment)







Eye/face protection

Use safety goggle with side protection.

Skin protection

hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

· type of material

FKM: fluoro-elastomer

material thickness

0,4 mm.

United Kingdom (en) Page 6 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection

Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid (fluid)
Colour colourless
Odour characteristic
Odour threshold No data available

Other physical and chemical parameters

pH (value) This information is not available.

Melting point/freezing point

-95 °C at 1.013 hPa
Initial boiling point and boiling range

110,6 °C at 1.013 hPa
Flash point

4,4 °C at 1.013 hPa
Evaporation rate

no data available
Flammability (solid, gas)

not relevant (fluid)

Explosive limits

lower explosion limit (LEL)
 upper explosion limit (UEL)
 7,1 vol% (308 g/m³)

Explosion limits of dust clouds not relevant
• lower explosion limit (LEL) 46 g/m³

• upper explosion limit (UEL) 308 g/m³

Vapour pressure 30,89 hPa at 21 $^{\circ}$ C Density 0,87 g /_{cm³} at 20 $^{\circ}$ C

Vapour density3,18 air = 1Bulk densityNot applicableRelative density3,18 air = 1

United Kingdom (en) Page 7 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

Solubility(ies)

Water solubility 573 ^{mg}/_I at 25 °C

Partition coefficient

n-octanol/water (log KOW) 2,73 (pH value: 7, 20 °C) (ECHA)

Auto-ignition temperature 480 °C - ECHA

Decomposition temperature no data available

Viscosity

kinematic viscosity
 dynamic viscosity
 0,7 mm²/s at 20 °C
 0,6 mPa s at 20 °C

Explosive properties none
Oxidising properties none

9.2 Other information

There is no additional information.

Refractive index 1,496

SECTION 10: Stability and reactivity

10.1 Reactivity

risk of ignition, Vapours can form explosive mixtures with air

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Danger of explosion: Perchlorates, Sulphuric acid, concentrated, Nitric acid, Acetic acid, Violent reaction with: Mineral acids, Strong oxidiser

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

different Rubber articles, plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

United Kingdom (en) Page 8 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: **7115**

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Shall not be classified as acutely toxic.

Exposure route	Endpoint	Value	Species	Source
oral	LD50	5580 ^{mg} / _{kg}	rat	ECHA
inhalation: vapour	LC50	28,1 ^{mg} / _l /4h	rat	ECHA
dermal	LD50	>5000 ^{mg} / _{kg}	rabbit	ECHA

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Reproductive toxicity:

Suspected of damaging the unborn child

• Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure (if inhaled).

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, presenting an aspiration hazard

• If in eyes

conjunctivitis (pink eye), causes slight to moderate irritation

If inhaled

causes slight to moderate irritation, cough, headache, poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness

• If on skin

has degreasing effect on the skin, Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation)

Other information

None.

United Kingdom (en) Page 9 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: **7115**

SECTION 12: Ecological information

12.1 Toxicity

acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	5,5 ^{mg} / _l	fish	ECHA	96 hours

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
LC50	3,78 ^{mg} / _l	aquatic invertebrates	ECHA	2 d
EC50	3,23 ^{mg} / _l	aquatic invertebrates	ECHA	7 d
LOEC	2,77 ^{mg} / _l	fish	ECHA	40 d
NOEC	1,39 ^{mg} / _l	fish	ECHA	40 d

12.2 Process of degradability

Theoretical Oxygen Demand: $3,13\,^{\rm g}/_{\rm g}$ Theoretical Carbon Dioxide: $3,343\,^{\rm mg}/_{\rm mg}$ Biochemical Oxygen Demand: $0,86\,^{\rm g}/_{\rm g}$

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW) 2,73 (pH value: 7, 20 °C)

BCF 90 (ECHA)

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Hazardous to water.

United Kingdom (en) Page 10 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

SECTION 13: Disposal considerations

13.1 Waste treatment methods

This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN number	1294
14.2	UN proper shipping name	TOLUENE
	Hazardous ingredients	Toluene
14.3	Transport hazard class(es)	
	Class	3 (flammable liquids)
14.4	Packing group	II (substance presenting medium danger)
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)
446	Curriel few	

14.6 Special precautions for user

UN number

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

1294

Proper shipping name	TOLUENE
Particulars in the transport document	UN1294, TOLUENE, 3, II, (D/E)
Class	3
Classification code	F1
Packing group	II
Danger label(s)	3

United Kingdom (en) Page 11 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E
Hazard identification No 33

• International Maritime Dangerous Goods Code (IMDG)

UN number 1294

Proper shipping name TOLUENE

Particulars in the shipper's declaration UN1294, TOLUENE, 3, II, 4,4°C c.c.

Class 3
Packing group II
Danger label(s) 3



Special provisions (SP)
Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category B

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)
 - Regulation 649/2012/EU concerning the export and import of hazardous chemicals (PIC) Not listed.
 - Regulation 1005/2009/EC on substances that deplete the ozone layer (ODS) Not listed.
 - Regulation 850/2004/EC on persistent organic pollutants (POP) Not listed.

United Kingdom (en) Page 12 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

List of substances subject to authorisation (REACH, Annex XIV)

not listed

Seveso Directive

96/8	96/82/EC (Seveso II)					
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) Notes		Notes		
7b	highly flammable	5.000	50.000	24)		

Notation

24)

Highly flammable liquids: substances and preparations having a flash point lower than 21 °C and which are not extremely flammable (risk phrase R 11, second indent)

2012/	2012/18/EU (Seveso III)					
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes		
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)		

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

• Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)

VOC content 100 %

Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content 100 %

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

not listed

Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)

not listed

National inventories

Substance is listed in the following national inventories:

- EINECS/ELINCS/NLP (Europe)
- REACH (Europe)

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

United Kingdom (en) Page 13 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations			
2006/15/EC	Comission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC			
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)			
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)			
BCF	BioConcentration Factor			
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)			
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures			
CMR	Carcinogenic, Mutagenic or toxic for Reproduction			
DMEL	Derived Minimal Effect Level			
DNEL	Derived No-Effect Level			
EH40/2005	EH40/2005 Workplace exposure limits, Table 1: List of approved workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)			
EINECS	European Inventory of Existing Commercial Chemical Substances			
ELINCS	European List of Notified Chemical Substances			
EmS	Emergency Schedule			
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations			
IMDG	International Maritime Dangerous Goods Code			
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008			
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant)			
NLP	No-Longer Polymer			
PBT	Persistent, Bioaccumulative and Toxic			
PNEC	Predicted No-Effect Concentration			
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals			
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)			
VOC	Volatile Organic Compounds			
vPvB	very Persistent and very Bioaccumulative			

Key literature references and sources for data

Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU Regulation (EC) No. 1272/2008 (CLP, EU GHS)

United Kingdom (en) Page 14 / 15

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU



Toluene ROTIPURAN® ≥99,5 %, p.a., ACS, ISO

article number: 7115

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	highly flammable liquid and vapour
H304	may be fatal if swallowed and enters airways
H315	causes skin irritation
H336	may cause drowsiness or dizziness
H361d	suspected of damaging the unborn child
H373	may cause damage to organs through prolonged or repeated exposure (if inhaled)

Disclaimer

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

United Kingdom (en) Page 15 / 15